Category:General Programming

This category is a catchall for categories related to programming and solving programming problems, which do not fall into the other main Technology Areas.

The portals below link to domain-specific portals of general programming problems:

- Windows Phone
- Java ME
- Qt
- Symbian C++
- Symbian Web Runtime

- Checking availability of Memory card in WRT . . hamishwillee
- Using timers in Nokia Asha web apps . . e4studio
- Simulating Pointer Events . . skalogir
- Detecting platform version at run time on Symbian . . hamishwillee
- Prepare your application for Nokia E6 . . pooja_1650
- Locking the keypad using Symbian C++ . . debjit.roy
- How to autostart an application on boot up using Startup List Management API . . vineet.jain
- List of Harmattan Packages . . gnuton
- Latest Qt and Qt mobility evaluation on Maemo . . achipa
- Working with QSystemNetworkInfo - System Information API - Part 1 . . girishpadia
- The Implications of Leaving in a Destructor . . hamishwillee
- The Implications of Leaving in a Constructor . . hamishwillee
- Calling Qt class methods from QML . . kratsan
- How to create the perfect WRT Icon . . Risalmin
- Connecting Qt signal to QML function . . kratsan

- Connecting Qt signal to QML function
- Calling Qt class methods from QML
- Latest Qt and Qt mobility evaluation on Maemo
- Prepare your application for Nokia E6
- Implementing a Singleton using Symbian CCoeStatic class
- How to autostart an application on boot up using Startup List Management API
- Listing installed applications in Symbian Web Runtime
- How-to create self-updating WRT widgets
- How to create the perfect WRT Icon
- Using timers in Nokia Asha web apps
- Showing date and time in Symbian Web Runtime
- Working with QSystemNetworkInfo - System Information API - Part 1
- Detecting platform version at run time on Symbian
- Base64 Encoding and Decoding
- Launching a native application from Qt

- Using timers in Nokia Asha web apps . . rebloor
- List of Harmattan Packages . . gnuton
- Prepare your application for Nokia E6 . . ltomuta
- The Implications of Leaving in a Destructor . . hamishwillee
- The Implications of Leaving in a Constructor . . hamishwillee
- Latest Qt and Qt mobility evaluation on Maemo . . achipa
- Calling Qt class methods from QML . . kratsan
- How to create the perfect WRT Icon . . Risalmin
- Connecting Qt signal to QML function . . kratsan
- Launching a midlet from Symbian C++ code . . ltomuta
- Handling Send key events in Phonebook Extension Plug-in . . Kbwiki
- Working with QSystemNetworkInfo - System Information API - Part 1 . . kiran10182

(C) Copyright Nokia 2014. All rights reserved.

- Retrieving system information using JSWrt object in Symbian Web Runtime . . Kbwiki
- Implementing widget runtime APIs with Nokia WRT functionality . . andrew.wharton
- Parsing UTF-8 encoded settings file . . isalento
- Prepare your application for Nokia E6 . . pooja_1650

Articles

B

- Base64 Encoding and Decoding

C

- Calling Qt class methods from QML
- Cancelling an asynchronous function call in Symbian Web Runtime
- Capturing the End (red) key during a call using Symbian C++
- Checking availability of Memory card in WRT
- Connecting Qt signal to QML function

D

- Deal with floating-point numbers in WRT environment
- Detecting platform version at run time on Symbian

E

- Exception handling in WRT

F

- Fixed-point math for Python
- Formatting an input dialog to accept large string of only digits

H

- Handling Send key events in Phonebook Extension Plug-in
- How to autostart an application on boot up using Startup List Management API
- How to check if the backlight is off and how to turn it on
- How to create the perfect WRT Icon

H cont.

- How to discover all installed applications
- How to get notification of user activity when the device has been idle
- How to import a variable from a module
- How to sort elements of RArray and RPointerArray
- How-to create self-updating WRT widgets

I

- Implementing a Singleton using Symbian CCoeStatic class
- Implementing widget runtime APIs with Nokia WRT functionality

L

- Latest Qt and Qt mobility evaluation on Maemo
- Launching a midlet from Symbian C++ code
- Launching a native application from Qt
- Launching an installed application from Symbian Web Runtime
- Layout conventions for Symbian C++
- List of Harmattan Packages
- Listing available fonts using Symbian C++
- Listing installed applications in Symbian Web Runtime

L cont.

- Locking the keypad using Symbian C++

P

- Parsing UTF-8 encoded settings file
- Prepare your application for Nokia E6

R

- Retrieving AutoLock time in WRT
- Retrieving Brightness of a device in WRT
- Retrieving Light timeout in WRT
- Retrieving Screen saver timeout in WRT
- Retrieving system information using JSWrt object in Symbian Web Runtime

S

- Showing date and time in Symbian Web Runtime
- Simulating Pointer Events

T

- Text conversion between 16-bit Unicode and UTF-8 using Symbian C++
- The Implications of Leaving in a Constructor
- The Implications of Leaving in a Destructor

U

- Using timers in Nokia Asha web apps

W

- Working with QSystemNetworkInfo - System Information API - Part 1

1

- 16位Unicode和UTF-8之间文本的转换

在

- 在Qt C++中调用QML中的Javascript Function

如

- 如何利用第三版Startup List

如 cont.

- 如何在通过中捕捉挂机键（红色）
- 如何构造一个能接收位数字的输入框
- 如何正确使用LeaveIfNull

如 cont.

- 如何锁住手机键盘

获

- 获得S60手机型号名

(C) Copyright Nokia 2014. All rights reserved.

Management API自启动程序

M

- Membuat Timer di Nokia Asha Web Apps

L

- Launching a midlet from Symbian C++ code

P

- Prepare your application for Nokia E6

U

- Using timers in Nokia Asha web apps

B

- Base64 Encoding and Decoding

C

- Calling Qt class methods from QML
- Cancelling an asynchronous function call in Symbian Web Runtime
- Capturing the End (red) key during a call using Symbian C++
- Checking availability of Memory card in WRT
- Connecting Qt signal to QML function

D

- Deal with floating-point numbers in WRT environment
- Detecting platform version at run time on Symbian

E

- Exception handling in WRT

F

- Formatting an input dialog to accept large string of only digits

H

- Handling Send key events in Phonebook Extension Plug-in
- How to autostart an application on boot up using Startup List Management API
- How to check if the backlight is off and how to turn it on
- How to create the perfect WRT Icon

C

- Calling Qt class methods from QML
- Connecting Qt signal to QML function

L

- Latest Qt and Qt mobility evaluation on Maemo
- Launching a native application from Qt
- List of Harmattan Packages

H cont.

- How to discover all installed applications
- How to get notification of user activity when the device has been idle
- How to sort elements of RArray and RPointerArray
- How-to create self-updating WRT widgets

I

- Implementing a Singleton using Symbian CCoeStatic class
- Implementing widget runtime APIs with Nokia WRT functionality

L

- Launching a midlet from Symbian C++ code
- Launching a native application from Qt
- Launching an installed application from Symbian Web Runtime
- Layout conventions for Symbian C++
- Listing available fonts using Symbian C++
- Listing installed applications in Symbian Web Runtime
- Locking the keypad using Symbian C++

P

- Parsing UTF-8 encoded settings file

P cont.

- Prepare your application for Nokia E6

R

- Retrieving AutoLock time in WRT
- Retrieving Brightness of a device in WRT
- Retrieving Light timeout in WRT
- Retrieving Screen saver timeout in WRT
- Retrieving system information using JSWrt object in Symbian Web Runtime

S

- Showing date and time in Symbian Web Runtime
- Simulating Pointer Events

T

- Text conversion between 16-bit Unicode and UTF-8 using Symbian C++
- The Implications of Leaving in a Constructor
- The Implications of Leaving in a Destructor

W

- Working with QSystemNetworkInfo - System Information API - Part 1

(C) Copyright Nokia 2014. All rights reserved.

W

- Working with QSystemNetworkInfo - System Information API - Part 1

A

- Create a list of platform threads in PySymbian
- FSCommandの紹介
- Flash Lite Comparison Chart
- Flash Lite Q&A
- Flash LiteとJava MEを接続する方法

A cont.

- Flash Lite機能の比較表
- How to attach symbols dynamically in ActionScript 2.0
- How to connect Flash Lite and Java ME
- Introduction to fscommands
- Launching the Web browser on S60 3rd Edition to open a specified URL

A cont.

- Random value generation in Open C
- Simulating Arrays in better way in Flash Lite 1.1
- Simulating Mouse Pointer in Flash Lite
- Simultaneously loading multiple images in Flash Lite
- Uso simples de Thread, em PySymbian

ADD_BODY_CLASS_BEGIN collapse_sub_categories ADD_BODY_CLASS_END

(C) Copyright Nokia 2014. All rights reserved.