Creating and registering a task handler with RScheduler

Archived: This article is **archived** because it is not considered relevant for third-party developers creating commercial solutions today. If you think this article is still relevant, let us know by adding the template {{ReviewForRemovalFromArchive|user=~~~~|*write your reason here*}}.

The article is believed to be still valid for the original topic scope.

Overview

This code snippet shows how a task handler EXE program can be created and registered when the class `RScheduler` is used to schedule Task Scheduler tasks. The client has to be registered with the scheduler before any tasks can be scheduled. The registration method is called `Register()` and it takes two parameters, the filename of the program to execute the tasks and the priority which is relative to other clients.

This snippet can be self-signed.

MMP file

The following libraries are required:

```
LIBRARY euser.lib
LIBRARY efsrv.lib
LIBRARY estor.lib
LIBRARY schsvr.lib
```

Source file (ExampleTaskHandler.exe)

```
#include <schinfo.h>
#include <schtask.h>
#include <s32file.h>

static void DoRunTaskL(RFile& aTaskFile)
{
    TInt taskCount(0);
    CFileStore* fileStore;
    RStoreReadStream readStream;

    fileStore = CDirectFileStore::FromLC(aTaskFile);
    readStream.OpenLC(*fileStore,fileStore->Root());

    //from schtask.h :
    //The root stream of the direct file store contains a 32-bit value, followed
    //by the external representations of one or more CScheduledTask objects. The
    //32-bit value is interpreted as a TInt32 and contains the number of CScheduledTask
    //objects that follow in the stream.
    taskCount = readStream.ReadInt32L();

    for (TInt index = 0; index < taskCount; index++)
        {
        CScheduledTask* task = CScheduledTask::NewLC(readStream);

        // Do something with the task info...
        //task->Info().iName;
        //task->Info().iTaskId;
        //task->ValidUntil();
        //HBufC* data = const_cast<HBufC*>(&(task->Data()));
```


(C) Copyright Nokia 2014. All rights reserved.

```
        CleanupStack::PopAndDestroy(task);
        }

    CleanupStack::PopAndDestroy(2); // fileStore, readStream
}

LOCAL_D TInt RunTask()
{
    TInt err(KErrNoMemory);
    CTrapCleanup* cleanup=CTrapCleanup::New();

    if (cleanup)
        {
        RFile file;

        //from schtask.h :
        //The registered program can use the RFile::AdoptFromCreator API in conjunction
        //with the APIs provided by this class to access the scheduled task file store
        err = file.AdoptFromCreator(TScheduledTaskFile::FsHandleIndex(),
                                    TScheduledTaskFile::FileHandleIndex());
        if (err != KErrNone)
            {
            return err;
            }

        TRAP(err, DoRunTaskL(file));

        file.Close();

        delete cleanup;
        }

    return err;
}

GLDEF_C TInt E32Main()
{
    return RunTask();
}
```

Header file

```
#ifndef __SCHEDULEREXAMPLEAPPUI_H__
#define __SCHEDULEREXAMPLEAPPUI_H__

#include <csch_cli.h> // RScheduler

class CSchedulerExampleAppUi : public CAknAppUi
    {
    //...
private:

    RScheduler iScheduler;

    };

#endif // __SCHEDULEREXAMPLEAPPUI_H__
```


(C) Copyright Nokia 2014. All rights reserved.

Source file

```
void CSchedulerExampleAppUi::ConstructL()
    {
    //...
    User::LeaveIfError(iScheduler.Connect());

    _LIT(KExampleTaskHandlerExe, "ExampleTaskHandler.exe");
    TFileName exampleHandler(KExampleTaskHandlerExe);

    User::LeaveIfError(iScheduler.Register(exampleHandler, CActive::EPriorityStandard));
    }

CSchedulerExampleAppUi::~CSchedulerExampleAppUi()
    {

    //...
    iScheduler.Close();
    }
```

Postconditions

The client is registered with the scheduler and ready to schedule Task Scheduler tasks. The program ExampleTaskHandler.exe is responsible for running scheduled tasks.

See also

- Archived:Creating persistent and transient schedules with RScheduler
- Archived:Creating a condition-based schedule with RScheduler
- Archived:Getting schedule and task info using RScheduler
- Archived:Getting schedule and task count using RScheduler
- Archived:Editing a schedule using RScheduler
- Archived:Deleting schedules and tasks using RScheduler

(C) Copyright Nokia 2014. All rights reserved.