Custom Avkon pop-up list

This article will show how to subclass CAknPopupList in order to customize its behavior. You can for example make it return the selected item after only one selection tap instead of two.

Summary

The solution is rather simple: subclass CAknPopupList and implement the handling of the tap and key events:

```
class CCustomPopupList : public CAknPopupList
 {
 public:
 // Constructors and destructor
 ...

private:

 TKeyResponse OfferKeyEventL(const TKeyEvent& aKeyEvent, TEventCode aType);

 void FocusChanged(TDrawNow aDrawNow);

 void HandleListBoxEventL(CEikListBox* aListBox, TListBoxEvent aEventType);

private:
 CAknSinglePopupMenuStyleListBox* iList;
 TBool iIsFocused;
 TInt& iCurrentItem;
 };
```

```
void CCustomPopupList::HandleListBoxEventL(CEikListBox* aListBox, TListBoxEvent
aEventType)
 {
 if ( aEventType == EEventEnterKeyPressed || aEventType == EEventItemSingleClicked ||
aEventType == EEventItemClicked )
  {
  AttemptExitL( ETrue );
  }
 else
  {
  CAknPopupList::HandleListBoxEventL( aListBox, aEventType );
  }
 }

TKeyResponse CCustomPopupList::OfferKeyEventL(const TKeyEvent& aKeyEvent, TEventCode
aType)
 {
 TKeyResponse response = EKeyWasNotConsumed;

 if ( aType == EEventKey && aKeyEvent.iCode == EKeyEscape )
         {
  AttemptExitL( EFalse );
  response = EKeyWasConsumed;
  }
 else
```


(C) Copyright Nokia 2014. All rights reserved.

```
  {
  response = iList->OfferKeyEventL(aKeyEvent, aType);
  }

 if ( aType == EEventKey && !iIsFocused )
  {
  switch ( aKeyEvent.iCode )
   {
   case EKeyUpArrow:
   case EKeyDownArrow:
   case EKeyDevice3:
   case EKeyEnter:
    iIsFocused = ETrue;
    iList->SetCurrentItemIndexAndDraw( iCurrentItem );
    break;
   default:
    break;
   }
  }

 return response;
 }
```

For a full example see \src\CustomPopupList.cpp and \inc\CustomPopupList.h in the attached project.

To use the new class:

```
TInt select=1;
CCustomPopupList* list = CCustomPopupList::NewL(select);
TInt popupOk = list->ExecuteLD();
if (popupOk)
 {
// _LIT(KMessage, "Selected: %d");
// TBuf<100> message;
// message.Format(KMessage, select);
// CAknInformationNote* informationNote = new (ELeave) CAknInformationNote;
// informationNote->ExecuteLD(message);
 }
```


(C) Copyright Nokia 2014. All rights reserved.

(C) Copyright Nokia 2014. All rights reserved.