Enabling and disabling all key sounds using CAknKeySoundSystem

Archived: This article is **archived** because it is not considered relevant for third-party developers creating commercial solutions today. If you think this article is still relevant, let us know by adding the template {{ReviewForRemovalFromArchive|user=~~~~|*write your reason here*}}.

The article is believed to be still valid for the original topic scope.

Overview

This code snippet shows how CAknKeySoundSystem is used to enable/disable all key sounds at once with the predefined key map list R_AVKON_SILENT_SKEY_LIST.

This snippet can be self-signed.

MMP file

The following libraries are required:

```
LIBRARY avkon.lib
LIBRARY eikcore.lib
LIBRARY eiksrv.lib
```

Header file

```
 #ifndef __TESTERAPPVIEW_H__
 #define __TESTERAPPVIEW_H__

// INCLUDES
#include <coecntrl.h>

class CAknKeySoundSystem;

class CTesterAppView : public CCoeControl
    {
 //...
private:
    CAknKeySoundSystem* iSoundSystem;
    TBool iSilentKeys;
    };

#endif // __TESTERAPPVIEW_H__
```

Source file

```
#include <avkon.rsg>  //R_AVKON_SILENT_SKEY_LIST
#include <aknsoundsystem.h>  // CAknKeySoundSystem
#include <aknappui.h>

void CTesterAppView::ConstructL(const TRect& aRect)
```


(C) Copyright Nokia 2014. All rights reserved.

```
    {
//...
    iSilentKeys = EFalse;
    iSoundSystem = static_cast<CAknAppUi*>(
    CEikonEnv::Static()->AppUi() )->KeySounds();

    if (!iSoundSystem)
        {
        //pointer to KeySound API object is null
        User::Leave(KErrGeneral);
        }
    }

CTesterAppView::~CTesterAppView()
    {
    iSoundSystem = NULL;
    }

// ---------------------------------------------------------------------------
// Disable all key sounds
// ---------------------------------------------------------------------------
//

void CTesterAppView::DisableAllKeySoundsL()
    {
    if ( iSoundSystem && !iSilentKeys )
        {
        //load key sound map from resources and push it to the context stack
        iSoundSystem->PushContextL( R_AVKON_SILENT_SKEY_LIST );

        //tell server to use this context stack for processing sounds
        iSoundSystem->BringToForeground();

        //lock this context to the foreground, other BringToForeground() calls
        //will be ignored until ReleaseContext() is called
        iSoundSystem->LockContext();

        iSilentKeys = ETrue;
        }
    }


// ---------------------------------------------------------------------------
// Enable all key sounds
// ---------------------------------------------------------------------------
//
void CTesterAppView::EnableAllKeySounds()
    {
    if ( iSoundSystem && iSilentKeys )
        {
        //release the locked context
        iSoundSystem->ReleaseContext();

        //pop the pushed context from the context stack
        iSoundSystem->PopContext();

        iSilentKeys = EFalse;
```


(C) Copyright Nokia 2014. All rights reserved.

```
        }
    }
```

Postconditions

The key sounds are enabled/disabled by calling the methods `DisableAllKeySoundsL()` and `EnableAllKeySounds()`.

See also

Archived:Enabling and disabling defined key sound using CAknKeySoundSystem

Archived:Using customized key sounds with CAknKeySoundSystem

(C) Copyright Nokia 2014. All rights reserved.