NFC Secure Element Example Java Card for Emulator

Warning: This example was created for the NFC implementation provided on Series 40 devices, and may include use of features not yet available for NFC on Symbian devices.

This is the code for the JAR file in order to emulate a smartcard (JavaCard) in the Nokia 6131 Emulator (no other emulator is supporting this example!). Click in the emulator on Internal Secure Card => Edit => and then chose the JAR compiled out of this code. Download appropriate NetBeans Project: File:TicketEmulation6131.zip.

```
package at.nfcresearch.wima.examples;

import com.nokia.phone.sdk.concept.srv.modules.nfc.cards.SecureCard;

public class TicketSmartCard extends SecureCard {
    // Command (APDU INS) for increading the value in the wallet
    private final static byte INS_INC = 0x01;

    // Command (APDU INS) for decreading the value in the wallet
    private final static byte INS_DEC = 0x02;

    // command (APDU INS) for reading the value in the wallet
    private final static byte INS_READ = 0x03;

    // variable holding the amount stored in the wallet.
    private byte value = (byte) 0x20;
    private static byte APDU_OK[] = {(byte) 0x90, 0x00};
    private static byte APDU_NOT_OK[] = {0x69, 0x00};

    public TicketSmartCard() {
        super();
    }

    public byte[] exchangeData(byte[] buf)  {
        byte cmd = buf[1];
        switch (cmd) {
            case INS_INC:
                if (value < 0xff) {
                    value++;
                }
                return APDU_OK;

            case INS_DEC:
                if (value > 0x00) {
                    value--;
                }
                return APDU_OK;

            case INS_READ:
                byte[] outBuffer = {value, APDU_OK[0], APDU_OK[1]};
                return outBuffer;
        }

        return APDU_NOT_OK;
    }
```


(C) Copyright Nokia 2014. All rights reserved.

```
    // Implemeation of Interface SecureCard
    public void createCardUID() {
        setCardUID("abcd");

    }

    // Implemeation of Interface SecureCard
    public void initSecureCard() {
        System.out.println("InnerCard initialized");
    }


}
```

And here is the code for the Nokia 6212 SDk

```
/**
 * @author Gerald Madlmayr
 * NFC Research Lab Hagenberg, www.nfc-research.at
 * @version 1.0
 *
 * Simulation of a SmartCard for the Emulator
 */

package at.nfcresearch.wima.examples;


import com.nokia.nfcsdk.nfcmgr.plugin.ISmartCardPluginData;
import com.nokia.nfcsdk.nfcmgr.plugin.SmartCardPlugin;

public class TicketSmartCard extends SmartCardPlugin {
 // Command (APDU INS) for increading the value in the wallet
 private final static byte INS_INC = 0x01;

 // Command (APDU INS) for decreading the value in the wallet
 private final static byte INS_DEC = 0x02;

 // command (APDU INS) for reading the value in the wallet
 private final static byte INS_READ = 0x03;

 // variable holding the amount stored in the wallet.
 private byte value = (byte) 0x20;

 private static byte APDU_OK[] = {(byte)0x90, 0x00};
 private static byte APDU_NOT_OK[] = {0x69, 0x00};

 public TicketSmartCard() {

 }

 public byte[] exchangeData(byte[] buf) throws Exception {
  byte cmd = buf[1];
  switch(cmd) {
   case INS_INC:
    if (value < 0xff)
     value++;
```


(C) Copyright Nokia 2014. All rights reserved.

```
    return APDU_OK;

   case INS_DEC:
    if (value > 0x00)
     value--;
    return APDU_OK;

   case INS_READ:
    byte[] outBuffer = {value, APDU_OK[0], APDU_OK[1]};
    return outBuffer;
  }

  return APDU_NOT_OK;
 }

 public String getName() {
  return "TicketSmartCard";
 }

 public void initialize(ISmartCardPluginData data) throws Exception {
  super.initialize(data);
 }

 public void uninitialize() {
 }
}
```


(C) Copyright Nokia 2014. All rights reserved.