# NFC Send UID from a tag to a Server

Warning: This example was created for the NFC implementation provided on Series 40 devices, and may include use of features not yet available for NFC on Symbian devices.

The following example consists out of two projects. One Java ME MIDlet, that uses a Nokia 6131 to read the UID of a tag and send it to a socket server. The second is very simple implementation of a Java SE socket server, that receives the UID and sends back an ok-message.

## The Java ME MIDlet

**Important:** Change the content of the variable "ip" according to your setup:

```
package at.nfcresearch.examples.uiddemo;

// Packages for contactless Communcation
import javax.microedition.contactless.ContactlessException;
import javax.microedition.contactless.DiscoveryManager;
import javax.microedition.contactless.TargetProperties;
import javax.microedition.contactless.TargetListener;
import javax.microedition.contactless.TargetType;

// Packages for GUI Stuff
import javax.microedition.lcdui.Alert;
import javax.microedition.lcdui.AlertType;
import javax.microedition.lcdui.Command;
import javax.microedition.lcdui.Display;
import javax.microedition.lcdui.Displayable;
import javax.microedition.lcdui.CommandListener;
import javax.microedition.lcdui.Form;

// Data Connection
import java.io.IOException;
import java.io.InputStream;
import java.io.OutputStream;

import javax.microedition.io.ConnectionNotFoundException;
import javax.microedition.io.Connector;
import javax.microedition.io.SocketConnection;


import javax.microedition.midlet.*;

public class UIDClient extends MIDlet implements TargetListener, CommandListener {
    // Display Stuff
    private Command exitCommand;
    private Form form;

    // change this IP Address according to your setup!!!
    private final static String ip = "socket://194.187.178.164:49997";

    public UIDClient() {

        // Create the GUI
        exitCommand = new Command("Exit", Command.EXIT, 1);
```


(C) Copyright Nokia 2014. All rights reserved.

```
        form = new Form("UIDClient");

        form.addCommand(exitCommand);
        form.append("Touch Tag to read ID.");
        form.setCommandListener(this);

        // Registration of the TargetListener for external contactless
        // Targets (in this RFID_TAG).
        try {
            DiscoveryManager dm = DiscoveryManager.getInstance();
            dm.addTargetListener(this, TargetType.NDEF_TAG);

        } catch (ContactlessException ce) {
            displayAlert("Unable to register TargetListener: " + ce.toString(),
AlertType.ERROR);
        }

    }

    public void startApp() {
        Display.getDisplay(this).setCurrent(form);
    }

    public void pauseApp() {
    }

    public void destroyApp(boolean unconditional) {
    }

    /**
     * Implementation of the Call-Back Function of the TargetListener
     * @param targetProperties: Array of Targets found by the Phone
     *
     */
    public void targetDetected(TargetProperties[] targetProperties) {

        // in case no targets found, exit the method
        if (targetProperties.length == 0) {
            return;
        }

        // show the UID of the first tag found
        TargetProperties tmp = targetProperties[0];
        displayAlert("UID read: " + tmp.getUid(), AlertType.INFO);

        // send data to server
        try {
            byte[] result = postViaSocketConnection(ip, tmp.getUid().getBytes());
            form.append("\nServer says: " + arrayToHex(result));
        } catch (Exception e) {
            form.append("Error: " + e.toString());
        }


    }

    /**
```


(C) Copyright Nokia 2014. All rights reserved.

```
     * Implementation of the Call-Back function of the CommandListener
     * @param command: command key pressed
     * @param displayable: associated displayable Object
     */
    public void commandAction(Command command, Displayable displayable) {
        if (command == exitCommand) {
            DiscoveryManager dm = DiscoveryManager.getInstance();
            dm.removeTargetListener(this, TargetType.NDEF_TAG);
            destroyApp(false);
            notifyDestroyed();
        }

    }

    private void displayAlert(String error, AlertType type) {
        Alert err = new Alert(form.getTitle(), error, null, type);
        Display.getDisplay(this).setCurrent(err, form);
    }

    // Establish a connectoin to a server.
    private byte[] postViaSocketConnection(String connectURL, byte[] inData) throws
IOException, SecurityException, ConnectionNotFoundException {

        SocketConnection sc = (SocketConnection) Connector.open(connectURL);
        sc.setSocketOption(SocketConnection.LINGER, 5);

        InputStream is = sc.openInputStream();
        OutputStream os = sc.openOutputStream();

        os.write(inData);
        int ch = 0;

        byte[] readin = new byte[0xFF];
        ch = is.read(readin);

        byte[] readReally = new byte[ch];
        System.arraycopy(readin, 0, readReally, 0, ch);

        if (is != null) {
            is.close();
        }
        if (os != null) {
            os.close();
        }
        if (sc != null) {
            sc.close();
        }
        return readReally;
    }

    private static String arrayToHex(byte[] data) {
        StringBuffer sb = new StringBuffer();

        for (int i = 0; i < data.length; i++) {
            String bs = Integer.toHexString(data[i] & 0xFF);
            if (bs.length() == 1) {
```


(C) Copyright Nokia 2014. All rights reserved.

```
                sb.append(0);
            }
            sb.append(bs);
            sb.append((i + 1) % 4 == 0 ? '\n' : ' ');
        }

        return sb.toString();
    }
}
```

## Java SE socket server implementation

The second application in the socket server (J2SE!!), that receives the data and sends back a 90 00 in order to confirm that the data was received.

Make sure that your firewall is not blocking the port. On a Windows machine you can use `netstat -a` in order to see all the open ports on your machine at the moment.

```
package at.nfcresearch.examples.uiddemo;

import java.io.IOException;
import java.io.InputStream;
import java.io.OutputStream;
import java.net.InetAddress;
import java.net.ServerSocket;
import java.net.Socket;
import java.net.UnknownHostException;

public class Server implements Runnable {

    private Socket m_socket;

    public Server(Socket socket) {
        m_socket = socket;
        new Thread(this).start();
    }

    public void run() {
        System.out.println("Thread opened -- Waiting for requets; ");

        // hier beginnen wir etwas einzulesen.
        try {

            InputStream input_stream;
            OutputStream output_stream;

            // getting the pointer to the streams
            input_stream = m_socket.getInputStream();
            output_stream = m_socket.getOutputStream();

            // reading data;
            byte bufferin[] = new byte[0xff];
            int len_cli = input_stream.read(bufferin);
            byte[] cli_buffer = new byte[len_cli];
            System.arraycopy(bufferin, 0, cli_buffer, 0, len_cli);
```


(C) Copyright Nokia 2014. All rights reserved.

```
            System.out.println(len_cli + " Bytes read");

            // print the read bbuffer
            System.out.println(new String(cli_buffer));

            // construct the return value
            byte bufferout[] = new byte[2];
            bufferout[0] = (byte) 0x90;
            bufferout[1] = (byte) 0x00;

            System.out.println("Information sent back;");

            output_stream.write(bufferout);
            output_stream.flush();

            input_stream.close();
            output_stream.close();

            // wait a bit, so that the data is sent for sure (!)
            Thread.sleep(100);

            m_socket.close();
        } catch (InterruptedException e) {
            System.out.println("Error on Seloop  Sleep: " + e.toString());

        } catch (IOException ie) {
            System.out.println("Error on opening the socket " + ie.toString());
        }

        System.out.println("connection to Tcp:/" +
m_socket.getRemoteSocketAddress().toString() + " closed");
    }

    public static void main(String[] args) {

        System.out.println("Server Started .....");
        ServerSocket tcp_server = null;
        InetAddress localhost = null;
        int serverPort = 49997;


        try {

            localhost = InetAddress.getLocalHost();

            // Öffnen eines neuen ServerSockets
            tcp_server = new ServerSocket(serverPort, 10, localhost);
            System.out.println("TcpEchoServer waiting for a connection at " +
tcp_server.getLocalSocketAddress());

        } catch (UnknownHostException e) {
            System.out.println("Error on opening the Socket Server: " + e.toString());
            System.exit(-1);
        } catch (IOException e) {
            System.out.println("OpenServerSocket faild: " + e.toString());
            System.exit(-1);
        }
```


(C) Copyright Nokia 2014. All rights reserved.

```
        // start endless loop
        while (true) {

            // Open Server Socket
            Socket tcp_socket = null;
            try {

                // wait for incoming connection; this Method is blocking!
                tcp_socket = tcp_server.accept();
                System.out.println("-----\nConnection to Tcp:/" +
tcp_socket.getRemoteSocketAddress().toString() + " established");

                // start a new thread to process this information
                new Server(tcp_socket);

            } catch (IOException e) {
                System.out.println("Error on trying to establish the connection : " +
e.toString());
                System.exit(-1);
            }
        }
    }
}
```


(C) Copyright Nokia 2014. All rights reserved.